

BSUBVM00/2.0IP/WDR WDR 1080P Network IR Bullet



Specifications

CAMERA

Image Sensor	1/2.9" Progressive Scan CMOS
Min. illumination	Color 0.1Lux;IR ON 0 Lux
Day & Night	ICR
Shutter Speed	1/5-1/20000
Auto Iris	Yes
Wide Dynamic Range	True WDR>120dB
Digital Noise Reduction	2D/3D
Lens	3.0-12mm Lens
FOV	87° ~ 35°
IR LED	17pcs
IR Range	30-40m

IMAGE

Video Compression	H.264 High/Main/Baseline Profile, MJPEG
Bit Rate (CBR/VBR)	Main stream:500kb-12000kb ;Sub stream 100kb-6000kb
Audio Compression	G.711 ,RAW_PCM
Max.Resolution	1920x1080/30fps
Stream	Stream1 1920x1080/1280x720 Stream 2 D1 to QVGA Stream 3 1920x1080 to QVGA
Image Setting	Rotate Mode,Saturation,Brightness,Contrast,Sharpness
HLC	Auto
9:16 Corridor mode	N/A
DIS	N/A
ROI	N/A
Defog	N/A

NETWORK

Network Protocols:	HTTP,HTTPS, TCP/IP, UDP/IP, RTSP, DHCP, NTP, PPoE, Unicast and Multicast supported.
Alarm Trigger	Motion Detection,Networkdisconnect,Diskalarm,I/O alarm
RTSP Video	Standard RFC2326, Support QuickTime / VLC Player.
Security	User security authentication, Reset, Hardware WatchDog
Web Language	English, Chinese,Polish,Italian,Portuguese,Spanish.
System Compatibility	Onvif

INTERFACE

Ethernet	1 Ethernet (10/100 Base-T) RJ-45 Connector
Audio I/O	1ch Audio In,1ch Audio Out
Alarm I/O	Default Not support,Optional1ch Alarm In,1ch Alarm Out
RS485	N/A
BNC Output	Yes
Reset Button	Yes
Edge Storage	Micro SD/SDHC slot ,Max 32GB


GENERAL

Power Supply	DC12V/POE
Power Consumption	5W(IR LED OFF) ; 11W (IR LED ON)
Operating Temperature	-10°C~+50°C
Operating Humidity	0% - 90% RH
Ingress Protection	IP66
Approvals	CE / FCC
Product Dimensions	φ 110×377mm
Product Weight	1680g

Key features

- 1/2.8" Progressive Scan CMOS
- VF Lens 3.0-12mm
- WDR>120dB
- Full HD 1080P
- Triple Streams
- IR Range 30-40m
- 3D DNR,ICR

Dimension



Accessories

