

UFACE 602

eSSL
Security at Fingertips



Feature	
Face Capacity	1200(1 :N), 3000(1:1)
Card Capacity	10,000 (optional)
Transaction Capacity	1,00,000
Fingerprint Capacity	2000



PRODUCT HIGHLIGHTS

Technical Specification		
Storage capacity	Face capacity	1200(1 :N), 3000(1:1)
	Fingerprints templates	2000 (Optional 4000)
	Card Storage	10,000 (Optional)
	Transaction storage	1,00,000
	Card reader	Yes
	CPU	1.0GHz
Biometric	Fingerprint sensor	500 DPI Optical sensor
	FAR	<=0.0001%
	FRR	<=1%
	Identification speed	<0.5 sec
	Algorithm Ver	10
Audio/Visual	Display	4.3-Inch Touch Screen
	Keypad	4*4 with 5 function Keys
	LED Indicator	Green/Red
	Schedule Bell/Speaker	Mini Speaker
Communication	Communication	TCP/IP, RS232/485, USB Host (Optional : Wifi, GPRS)
	Push data	Yes
	Standard features	DLST
Power & environment	Power Supply	12V 3A
	Operating Temperature	0°C - 45°C
	Operating Humidity	20% - 80%
	Dimension	194.1x169x109.0mm



PRODUCT HIGHLIGHTS

Access control	Wiegand	Output
	Relay	12 V relay for lock EM lock, Bolt Lock or Strike lock
	Support Fire Alarm	Yes
	Door Sensor	Yes
	Anti Passback	Yes
	Door Bell	Yes
Exit Readers	Support exit readers	Yes
Optional	Battery	7.4V 2000 mAh Backup Battery
	Card readers	No
	Communication	No
	Sensor	No
Compatibility		Compatible with Multi Door controllers via weigand
		External Speaker output available (Optional)
		External Bulb output available (Optional)
		Support External Printer
Compatible Software and SDK		Smart office suite desktop and web
		etime track lite desktop & web
		SDK for desktop applications
		Web based Device Manager/ePush server using Push data. Helps developers & integrators
		Supports 3rd Party Payroll/HRMS/ERP and Other applications
Major Applications		Time & Attendance , Canteen management, School attendance,
		Production Management, Gym & clubs