

CP- TNW-HP4H5-6

9 Port Fast Ethernet Switch with 4 POE



Main Features

- 1pc 100Mbps uplink Ethernet port, 8 pcs100Mbps downlink Ethernet Ports with 4 Ports PoE
- One key CCTV mode, $1\sim8$ downlink ports can only communicate with uplink ports , Restrain network storm under 2Mbps; Extend downlink ports transmission distance to 250m
- Standard: Meet IEEE802.3, IEEE802.3u , IEEE802.3 af/at standards, PoE use End- Span, the spare cable can be of other use
- Protection: Excellent anti-thunder, anti-static and anti-interference ability





CP- TNW-HP4H5-6

9 Port Fast Ethernet Switch with 4 POE

Specification

Feature

Uplink Ports 1 x 10/100Base-TX Ethernet Ports

Downlink Ports 8 x 10/100Base-TX Ethernet Ports(4 Ports PoE)

Network Standard Support IEEE 802.3/802.3u/IEEE802.3x

Switch Capacity 1.8Gbps
Packet Forwarding Rate 1.34 Mpps

Exchange Type Storage & Forwarding

Buffer 768k MAC Address List 2K

PoE Standard 802.3af/at(PSE)
PoE Mode End-span
PoE Power Supply 1/2(+), 3/6(-)

PoE Output Single PoE Output≤30W(54V DC), Whole machine PoE output≤60W

Surge Immunity 6KV: IEC61000-4-5

PoE Power Budget 60W

CCTV Mode Downlink ports only communicate with uplink ports , Extend transmission distance to 250m

(Downlink Ports), Rate:10Mbps(Downlink Ports)

ESD Protection Contact discharge 6K, Air discharge 8KV, Per: IEC61000-4-2

Power Source DC 48V~57V

Power Consumption 5W

Operating Temperature $-10^{\circ}\text{C} \sim +55^{\circ}\text{C}$ Storage Temperature $-40^{\circ}\text{C} \sim +85^{\circ}\text{C}$

Humidity 5%-95%(Non-condensing)
Dimensions 200mm x 101.8mm x 27mm

Color Gray Weight 500g



