

## CP- UVR-1616K1-S

16 Ch. 1080P Cosmic HD DVR





#### **Main Features**

- Auto Adaptive HDCVI/AHD/TVI/CVBS/IP signals
- Support upto 5MP IP Camera
- All channel 1080P Non-Realtime Recording
- H.264+ /H.264 dual-stream Video Compression
- HDMI / VGA Simultaneous Video Output
- Support 1 SATA HDD up to 6TB, 2 USB(1 USB 2.0, 1 USB 3.0)
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS, KVMS Pro



















## CP- UVR-1616K1-S

#### 16 Ch. 1080P Cosmic HD DVR



Feature Specification

Processor Embedded processor

IP Camera Input 16+8: each channel up to 5MP

Operating System Embedded LINUX

Two-way Talk Reuse audio in (channel 1)/out, RCA

User Interface GUI

Video Input 16 channel, BNC Video Output 1 HDMI, 1 VGA

Video Standard Analog: NTSC(525Line, 60f/s), PAL(625Line, 50f/s)

Compression H.264+/H.264

Video Resolution  $1920 \times 1080, 1280 \times 1024, 1280 \times 720, 1024 \times 768$ 

Video Recording

Main stream: 1080P(1~15fps) 1080N/720P/960H/D1/HD1/BCIF/CIF/QCIF (1~25/30fps) , Sub

stream: D1/CIF/QCIF(1~25/30fps)

Video Display Split 1/4/8/9/16/25 **Audio Input** 16 channel **Audio Output** 1 channel Motion Detection Supports Video Loss Supports Camera Blank Supports Alarm Input 16 channel Alarm Output 3 channel

Hard Disk 1 SATA port, up to 6TB
Smart Phone iPhone, iPad, Android, Phone

Trigger Events Recording, PTZ, Tour, Alarm Out, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tips

Recording Mode Manual, Schedule (Regular, Continuous), MD (Video detection: Motion Detection, Video

Loss, Tampering), Alarm, Stop

Search Mode Time /Date, Alarm, MD and Exact Search (accurate to second)

Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous

camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom

Backup Mode USB Device/Network

Interface Ports 1 HDMI, 1 VGA, 2 USB(1 USB 2.0 , 1 USB 3.0), 1 RS485, 1 RJ45

Record Interval 1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec





# CP- UVR-1616K1-S

16 Ch. 1080P Cosmic HD DVR



**Feature** 

Max User Account

Ethernet

Protocols

Power Supply

Power Consumption
Working Temp

Dimensions

Weight

**Specification** 

128 users

RJ-45 port (1000M)

HTTP, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS,

FTP, Alarm Server, P2P, IP Search, ONVIF 2.4.1, CGI Conformant

DC12V/2A

<10W(without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

325mm x 255mm x 55mm

1.5KG (without HDD)



