

CP- UVR-0400C1-V3**4 Ch. 720P HDCVI DVR****Main Features**

- Support HDCVI / Analog Video input
- All channel 720P Realtime Recording
- H.264 dual-stream Video Compression
- HDMI / VGA Simultaneous Video Output
- Support 1 SATA HDD up to 6TB, 2 USB2.0
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software:KVMS, KVMS Pro



CP- UVR-0400C1-V3

4 Ch. 720P HDCVI DVR



Feature

Processor
Operating System
Two-way Talk
User Interface
Video Input
Video Output
Video Standard
Compression

Video Resolution

Video Recording

Video Display Split

Privacy Masking

Motion Detection

Video Loss

Camera Blank

Smart Phone

Hard Disk

Trigger Events

Recording Mode

Search Mode

Playback

Backup Mode

Max User Account

Interface Ports

Record Interval

Ethernet

Protocols

Specification

Embedded processor

Embedded LINUX

Reuse audio input/output channel 1

GUI

4 channel, BNC

1 HDMI, 1 VGA

Analog: NTSC/PAL, HDCVI: 720P HDCVI Camera

H.264 / G.711

720P(1280×720) / 960H(960×576/960×480) / D1(704×576/704×480) / HD1
(352×576/352×480) / BCIF(704×288 / 704×240) CIF(352×288/352×240) / QCIF
(176×144/176×120)

Main Stream: 720P(1~25/30fps)+3*(1~12/15fps) / 960H/D1/HD1/BCIF/CIF/QCIF
(1~25/30fps), Extra Stream: CIF/QCIF(1~7fps)

1/4/6

4 rectangular zones (each camera)

Supports

Supports

Supports

iPhone, iPad, Android, Windows Phone

1 SATA port, up to 6TB

Recording, PTZ, Tour, Video Push, Email, FTP, Spot, Buzzer & Screen tips

Manual, Schedule(Regular(Continuous), MD), Stop

Time/Date, MD & Exact search (accurate to second)

Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup, selection, Digital zoom

USB Device/Internal SATA burner.

128 users

1 HDMI, 1 VGA, 2 USB2

1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec

RJ-45 port (10/100M)

HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, SNMP, P2P, ONVIF Version 2.4 conformance





CP- UVR-0400C1-V3

4 Ch. 720P HDCVI DVR



Feature

Power Supply
Power Consumption
Working Temp
Dimensions
Weight

Specification

DC12V/4A
10W(without HDD)
-10 ~+55°C / 10~90%RH / 86~106kpa
260mm × 220mm × 44mm
1.05Kg(without HDD)

