

CP- UVR-0401E1-S

4 Ch. 1080P Lite Cosmic HD DVR





Main Features

- Auto Adaptive HDCVI/AHD/TVI/CVBS signals
- Support upto 5MP IP Camera
- All channel 1080P Lite Realtime Recording
- H.264 dual-stream Video Compression
- HDMI / VGA Simultaneous Video Output
- Support 1 SATA HDD up to 6TB, 2 USB2.0
- Mobile Software: iCMOB, gCMOB
- CMS Software:KVMS, KVMS Pro



















CP- UVR-0401E1-S

4 Ch. 1080P Lite Cosmic HD DVR



Feature Specification

Processor Embedded processor
Operating System Embedded LINUX

IP Camera Input 4+1: each channel up to 2MP
Two-way Talk Reuse audio in/out, RCA

User Interface GUI

Video Input 4 channel, BNC
Video Output 1 HDMI, 1 VGA

Video Standard Analog: NTSC(525Line, 60f/s), PAL(625Line, 50f/s)

Compression H.264

Video Resolution $1920 \times 1080, 1280 \times 1024, 1280 \times 720, 1024 \times 768$

Video Recording

Main Stream: 1080N/720P/960H/D1/HD1/BCIF/CIF/QCIF (1~25/30fps), Extra Stream: D1/CIF/

 $QCIF (1{\sim}25/30 fps)$

Video Display Split 1/4/6

Audio Input 1 channel, RCA
Audio Output 1 channel, RCA
Motion Detection Supports

Video Loss Supports
Camera Blank Supports

Recording Mode

Smart Phone iPhone, iPad, Android, Phone
Hard Disk 1 SATA port, up to 6TB

Trigger Events Recording, PTZ, Tour, Alarm Out, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tips

Manual, Schedule (Regular, Continuous), MD (Video detection: Motion Detection, Video

Loss, Tampering), Alarm, Stop

Search Mode Time /Date, Alarm, MD and Exact Search (accurate to second)

Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous

camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom

Backup Mode USB Device/Network

Max User Account 128 users

Record Interval 1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec

Interface Ports 1 HDMI, 1 VGA, 2 USB2.0, 1 RS485

Ethernet RJ-45 port (10/100M)







4 Ch. 1080P Lite Cosmic HD DVR



Feature

Protocols

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

Specification

HTTP, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE,DDNS, FTP, Alarm Server,P2P, IP Search, ONVIF 2.4.1, CGI Conformant

DC12V/2A

<10W(without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

260mm ×236mm ×48mm

0.75KG(without HDD)



