

**CP- UVR-0404K1-S****4 Ch. 1080P Cosmic HD DVR****COSMIC**  
HD DVR**Main Features**

- Auto Adaptive HDCVI/AHD/TVI/CVBS/IP signals
- Support upto 5MP IP Camera
- All channel 1080P Non-Realtime Recording
- H.264+ /H.264 dual-stream Video Compression
- HDMI / VGA Simultaneous Video Output
- Support 1 SATA HDD up to 6TB, 2 USB2.0
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS, KVMS Pro



*\*Product casing and specifications are subject to change without prior notice*

# CP- UVR-0404K1-S

## 4 Ch. 1080P Cosmic HD DVR

**COSMIC**  
HD DVR

### Feature

Processor  
IP Camera Input  
Operating System  
Two-way Talk  
User Interface  
Video Input  
Video Output  
Video Standard  
Compression  
Video Resolution  
Video Recording  
Video Display Split  
Audio Input  
Audio Output  
Motion Detection  
Video Loss  
Camera Blank  
Alarm Input  
Alarm Output  
Hard Disk  
Smart Phone  
Trigger Events  
Recording Mode  
Search Mode  
Playback  
Backup Mode  
Max User Account

### Specification

Embedded processor  
4+2: each channel up to 5MP  
Embedded LINUX  
Reuse audio in (channel 1)/out, RCA  
GUI  
4 channel, BNC  
1 HDMI, 1 VGA  
Analog: NTSC(525Line, 60f/s), PAL(625Line, 50f/s)  
H.264+/H.264  
1920 × 1080, 1280 × 1024, 1280 × 720, 1024 × 768  
Main stream: 1080P(1~15fps) 1080N/720P/960H/D1/HD1/BCIF/CIF/QCIF (1~25/30fps) , Sub stream: D1/CIF/QCIF(1~25/30fps)  
1/4/6  
4 channel  
1 channel  
Supports  
Supports  
Supports  
4 channel  
3 channel  
1 SATA port, up to 6TB  
iPhone, iPad, Android, Phone  
Recording, PTZ, Tour, Alarm Out, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tips  
Manual, Schedule (Regular, Continuous), MD (Video detection: Motion Detection, Video Loss, Tampering), Alarm, Stop  
Time /Date, Alarm, MD and Exact Search (accurate to second)  
Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom  
USB Device/Network  
128 users

# CP- UVR-0404K1-S

## 4 Ch. 1080P Cosmic HD DVR

**COSMIC**  
HD DVR

### Feature

Record Interval

Interface Ports

Ethernet

Protocols

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

### Specification

1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec

1 HDMI, 1 VGA, 2 USB2.0, 1 RS485, 1 RJ45

RJ-45 port (100M)

HTTP, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, P2P, IP Search, ONVIF 2.4.1, CGI Conformant

DC12V/2A

<10W(without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

325mm x 255mm x 55mm

1.5KG (without HDD)