

CP- UVR-0404K1-V3

4 Ch. 720P HDCVI DVR



Main Features

- Support HDCVI/Analog/IP Video input
- All channel 1080N/720P realtime or 1080P non-realtime recording
- H.264 dual-stream Video Compression
- HDMI / VGA Simultaneous Video Output
- Support 1SATA HDD up to 6TB, 2 USB2.0
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software:KVMS, KVMS Pro



CP- UVR-0404K1-V3

4 Ch. 720P HDCVI DVR



Feature

Processor
Operating System
Two-way Talk
User Interface
Video Input
Video Output
Video Standard
Compression
Video Resolution
Video Recording
Video Display Split
Privacy Masking
Audio Input
Audio Output
Motion Detection
Video Loss
Camera Blank
Alarm Input
Alarm Output
Smart Phone
Hard Disk
Trigger Events
Recording Mode
Search Mode

Playback

Backup Mode
Interface Ports
Record Interval
Max User Account

Specification

Embedded processor
Embedded LINUX
Reuse audio input/output channel 1
GUI
4 channel, BNC
1 HDMI, 1 VGA
Analog: NTSC/ PAL, HDCVI: 1080P/720P ,IP:4+2 up to 5Mp
H.264 / G.711
1920×1080, 1280×1024, 1280×720, 1024×768
Main Stream:1080P(1~15fps) 1080N/720P/960H/D1/HD1/BCIF/CIF/QCIF (1~25/30fps) Extra Stream:D1/CIF/QCIF(1~15fps)
1/4/6
4 rectangular zones (each camera)
4 channel, RCA
1 channel, RCA
Supports
Supports
Supports
4 channel
3 Channel
iPhone, iPad, Android, Windows Phone
1 SATA port, up to 6TB
Recording, PTZ, Tour, Video Push, Email, FTP, Spot, Buzzer & Screen tips
Manual, Schedule(Regular(Continuous), MD), Stop
Time/Date, MD & Exact search (accurate to second)

Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup, selection, Digital zoom

USB Device/Internal SATA burner/Network
1 HDMI, 1 VGA, 2 USB2.0
1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
128 users

CP- UVR-0404K1-V3

4 Ch. 720P HDCVI DVR



Feature

Ethernet

Protocols

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

Specification

RJ-45 port (10/100M)

HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, SNMP, P2P

DC12V/2A

10W(without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

325mm × 255mm × 55mm

1.5KG(without HDD)