







## **Main Features**

- H.264 dual-stream video compression
- All channel AHD-H Realtime Encoding
- 8Ch. 1080N / 4Ch. AHD-H @12fps
- HDMI / VGA simultaneous video output
- Support 1 SATA HDD up to 6TB, 2 USB2.0
- Mobile Software: RMOB
- CMS Software: RVMS





















**Feature** Specification

Processor High performance embedded microprocessor

Operating System Embedded LINUX

IP Camera Input 8 cameras

User Interface GUI

Video Input 8 channel, BNC
Video Output 1 VGA,1HDMI
Video Standard NTSC/PAL
Compression H.264/G.711A

Video Recording 8Ch. @1080N/720P(1~12fps) / 4Ch. @1080P(1-15fps)

Video Display Split 1/4/8/9
Audio Input 4ch RCA
Audio Output 1ch RCA

Hard Disk 1SATA port, up to 6 TB Smart Phone iPhone, Android

Recording Mode Manual>alarm>motion detection>timing

Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous

camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom

Backup Mode Network backup - USB HDD- USB writer, SATA writer

Interface Ports 2 USB 2.0, 1 RS485, 1 RJ45

Wi-Fi Support 3G, WIFI(expand via USB)

Ethernet RJ45 10M/100M Adaptive Ethernet port

Power Supply DC12V
Power Consumption DC12V/2A
Working Temp -10 ~+55°C

Dimensions 255mm(L) x 236mm(W) x 44mm(H)

Weight 1.8Kg.



