

CP- UVR-0801E1S-S

8 Ch. 1080P Lite Cosmic HD DVR

COSMIC
HD DVR



Main Features

- Auto Adaptive HDCVI/AHD/TVI/CVBS signals
- Support upto 5MP IP Camera
- All channel 1080P Lite Non-Realtime Recording
- Support 1 SATA HDD up to 6TB, 2 USB2.0
- HDMI / VGA Simultaneous Video Output
- H.264 dual-stream Video Compression
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS, KVMS Pro



CP- UVR-0801E1S-S

8 Ch. 1080P Lite Cosmic HD DVR

COSMIC
HD DVR

Feature

Processor
IP Camera Input
Operating System
Two-way Talk
User Interface
Video Input
HD Camera Input
Video Output
Compression
Video Resolution
Video Recording
Video Display Split
Privacy Masking
Audio Input
Audio Output
Motion Detection
Video Loss
Camera Blank
Smart Phone
Hard Disk
Trigger Events
Recording Mode
Search Mode
Playback
Backup Mode
Interface Ports
Max User Account
Record Interval

Specification

Embedded processor
8+2: each channel up to 5MP
Embedded LINUX
1 Channel Input, 1 Channel Output, RCA
GUI
8 channel, BNC
8 Channel HDCVI Camera Input
1 HDMI, 1 VGA
H.264
1920 × 1080, 1280 × 1024, 1280 × 720, 1024 × 768
Main Stream: 1080N(12fps)/720P(15fps)/960H/D1/HD1/BCIF/CIF/QCIF (1~25/30fps), Sub stream: CIF/QCIF(1~7fps)
1/4/8/9/16
Up to 4 areas
1 channel, RCA
1 channel, RCA
MD Zones: 396 (22 × 18)
Supports
Supports
iPhone, iPad, Android Phone
1 SATA port, up to 6TB
Recording, PTZ, Tour, Alarm Out, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tips
Manual, Schedule (Regular, Continuous), MD (Video detection: Motion Detection, Video Loss, Tampering), Alarm, Stop
Time/Date, MD & Exact search (accurate to second)
Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup, selection, Digital zoom
USB Device/Network
1 HDMI, 1 VGA, 2 USB2.0, 1 RS485
128 users
1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec



CP- UVR-0801E1S-S

8 Ch. 1080P Lite Cosmic HD DVR

COSMIC
HD DVR

Feature

Ethernet

Protocols

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

Specification

RJ-45 port (10/100M)

HTTP, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, P2P, ONVIF Version 2.4 conformance

DC12V/2A

<15W (Without HDD)

-10°C ~ +55°C (+14°F ~ +131°F), 86 ~ 106kpa / 0 ~ 90% RH

205mm x 211mm x 45mm

0.5kg (1.1lb) (without HDD)