

CP- SMR-H0804-S11-PG

8 Ch. WD1 + 4 Ch. 720P(IPC) / (WD1) H.264 Mobile DVR



Main Features

- Supports 8 channels WD1 + 4 channels IPC (720P) or 4 channels WD1 + 8 channels IPC (720P)
- Supports Hard Disk for main recording
- Supports 360 degree anti-vibration
- Supports GPS for location tracking, Supports USB2.0
- Supports SD card for mirror recording
- Supports Built-in heater (optional)
- Built-in G-sensor
- Pre-recording max. 60 mins
- Built-in 3G/4G for live view and remote management



CP- SMR-H0804-S11-PG

8 Ch. WD1 + 4 Ch. 720P(IPC) / (WD1) H.264 Mobile DVR

Feature

Operating System

Control Mode

Operation Interface

Video Systems

Total Resource

Video Input

Video Output

Recording Mode

Audio Input

Audio Output

Pre-recording

Image Resolution

Post-recording

Display Split

OSD

GPS

Playback

Mirror Recording

Image Quality

Sensors

Search Mode

USB

Ethernet

Video/Audio Compression

Panel

3G Support

Storage

Specification

Linux 3.0.8

Easy Check, IR Remote Control, Network, Mouse

Semi-transparent GUI

Electrical level: 1Vpp Impedance: 75Ω NTSC/PAL Optional

(8 x 25)FPS WD1 @ PAL / (8 x 30)FPS WD1 @ NTSC +(4 x 30)FPS 720P or (4 x 25)FPS WD1 @ PAL / (4 x 30)FPS WD1 @ NTSC +(4 x 30)FPS 720P

8 Channel WD1+4 Channel IPC(720P)/4 Channel WD1+8 Channel IPC (720P)

2 channels

Manual/schedule/Alarm (sensor trigger, speed, acceleration, video loss, temperature)

8 Channels(12 channels if connects with IPCX4)

2 Channels

0~60 minutes

Analog: PAL: WD1, WHD1, WCIF, D1, HD1, CIF, NTSC, WD1, WHD1, WCIF, D1, HD1, CIF; Digital: 720P

0-30 minutes

1/4/9

GPS/BD information, alarm, temperature, acceleration, voltage, device information, software version, MCU version, network status

Location tracking, speed detection and time sync

1/4 channels by local playback

Supports

8 Levels adjustable

8 Inputs, 2 Outputs

Date/time, channel, event

USB 2.0 × 2

RJ45(1000M)

H.264/ADPCM

Interface(CP4)(Optional)

Supports 3G/4G, EVDO/WCDMA/TDD-LTE/FDD-LTE

Supports 2.5" hard disk up to 2TB, SD Card x 1

CP- SMR-H0804-S11-PG

8 Ch. WD1 + 4 Ch. 720P(IPC) / (WD1) H.264 Mobile DVR

Feature

Serial Ports
Power Input
Power Output
Dimension (WxHxD)
Weight
Operating Temperature
Relatively Operating Humidity
Certification

Specification

RS232 × 2 / RS485 × 2
DC8-36V
1A@12V, 1A@5V
292.5mm x 215mm x 91.6mm
2.6 kg
-40°C - +70°C (With heater) or -10°C - +70°C
8%~90%
CE, FCC