

CP- UNC-TB20ZL6S-VMD-V2

2 MP Full HD IR Bullet Camera - 60Mtr.



Main Features

- 1/2.7" 2Megapixel progressive CMOS
- Max 25/30fps@1080P
- H.264 and MJPEG dual-stream encoding
- WDR(120dB), Day/Night (ICR), 3DNR, AWB, AGC, BLC
- 2.7 -12mm Motorized Lens
- IR Range of 60 Mtrs, IP67,PoE, SD Card
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro, vOptimus Pro



*Product casing and specifications are subject to change without prior notice

CP- UNC-TB20ZL6S-VMD-V2

2 MP Full HD IR Bullet Camera - 60Mtr.



Feature

Image Sensor
Effective Pixels
Minimum Illumination
Shutter Speed
White Balance
Lens
Gain Control (AGC)
Back Light Compensation
Video Compression
S/N Ratio
Video Streaming
Resolution
Privacy Mask
ICR
Audio Input
Audio Compression
Audio Output
Alarm IN
Alarm Out
WDR
Protocol
Ethernet
User Account
IR
Smart Phone
Micro SD
Operating Temperature
Power Source
Power Consumption

Specification

1/2.7" 2MP PS scan CMOS
1920(H)x1080(V)
0.1Lux/F1.4(Color), 0Lux/F1.4(IR on)
Auto/Manual, 1/3(4)~1/100000s
Auto/Manual
2.7 -12mm Motorized Lens
Auto/Manual
BLC/ HLC/ WDR
H.264/ H.264H/ MJPEG
More than 50dB
Main Stream:1080P (1 ~ 25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps)
1080P(1920x1080)/1.3M(1280x960)/720P(1280x720)/D1(704x576/704x480)/CIF
(352x288/352x240)
Up to 4 areas
Auto (ICR)/Color/B/W
1 channel In
G.711a/ G.711u
1 channel Out
1 channel In
1 channel Out
True WDR(120dB)
IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP,RTSP, RTP, SMTP, NTP,
DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, 802.1x, ONVIF, PSIA, CGI
RJ-45 (10/100Base-T)
20 Users
IR Range of 60 Mtr.
iPhone, iPad, Android Phone
Micro SD , Max 128GB
-30°C~+60°C , Less than 95%RH
DC12V, PoE (802.3af)
Max 13W

CP- UNC-TB20ZL6S-VMD-V2

2 MP Full HD IR Bullet Camera - 60Mtr.



Feature

Weatherproof Standard

Dimension

Weight

Specification

IP67

72mmx80mmx212.8mm

0.65kg