

CP- UNC-TD4K08L3

4K Full HD IR Bullet Camera - 30Mtr.



Main Features

- 1/2.3" 4K PS CMOS Image Sensor
- 7fps@4K
- H.264 and MJPEG dual-stream encoding
- DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC
- 4mm fixed lens
- IR Range of 30 Mtrs, IP66, PoE
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMs Pro, vOptimus Pro



CP- UNC-TD4K08L3

4K Full HD IR Bullet Camera - 30Mtr.

Feature

Image Sensor
Minimum Illumination
Shutter Speed
White Balance
Lens
Gain Control(AGC)
S/N Ratio
Back Light Compensation
Video Compression

Video Streaming

Resolution

Privacy Mask
ICR

Protocol

Smart Detection

Ethernet

User Account

IR

Smart Phone

Operating Temperature

Power Source

Power Consumption

Weatherproof Standard

Dimension

Weight

Specification

1/2.3" 4K progressive scan CMOS
0.1Lux/F1.6 (Color), 0Lux/F1.6(IR on)
Auto/Manual, 1/3(4)~1/10000s
Auto/Manual
4mm
Auto/Manual
More than 50dB
BLC / HLC / DWDR
N/A

Main Stream: 4K(1~7fps)/3M/1080P/ (1 ~ 25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps),

4K(3840× 2160)3M(2048× 1536)/1080P(1920× 1080) /720P(1280× 720) /D1(704× 576/704× 480) / CIF(352× 288/352× 240)

Up to 4 areas
Auto(ICR)/Color/B/W

IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP,RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS,Bonjour, ONVIF, PSIA, CGI

Tripwire, Intrusion, Scene Change, Face detect

RJ-45 (10/100Base-T)

20 Users

IR Range of 30 Mtr.

iPhone, iPad, Android, Windows Phone

-40°C~+60°C, Less than 95% RH

DC12V, PoE (802.3af)

Max 7.5W

IP66

178.4mm × 70mm × 69.9mm

528g(683.4g with packaging)