

CP- UNC-TH4KZR5-VM

4K Network Array Bullet Camera - 50Mtr.



Main Features

- 1/1.7\" 12 MP PS CMOS Image Sensor
- Max 20fps@12Mp, 25/30fps@4K
- H.265, H.264 and MJPEG dual-stream encoding
- DWDR, Day/Night (ICR), 3D-DNR, AWB, AGC, BLC
- 4.1 -16.4mm Motorized Lens
- IR Range of 50 Mtrs, IP67, IK10, PoE Plus
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro, vOptimus Pro



*Product casing and specifications are subject to change without prior notice

CP- UNC-TH4KZR5-VM

4K Network Array Bullet Camera - 50Mtr.



Feature

Image Sensor
Effective Pixels
Minimum Illumination
Shutter Speed
White Balance
Lens
Gain Control (AGC)
Video Compression
Back Light Compensation
S/N Ratio

Video Streaming

Resolution

Motion detection

Special Feature

ICR

ROI

Audio Input

Audio Output

Audio Compression

Alarm IN

Alarm Out

Pre/Post Alarm Buffer

Watermark

Protocol

Smart Detection

Ethernet

Specification

1/1.7" 12MP CMOS

4000(H) x 3000(V)

0.01Lux/F1.53(Color,1/3s,30IRE) 0.1Lux/F1.53(Color,1/30s,30IRE) 0Lux/F1.53(IR on)

Auto/Manual, 1/1~1/100000s

Auto/Sunny/Night/Outdoor/Customized

4.1 - 16.4mm Motorized , Auto Iris

Auto/Manual

H.265 / H.264 / MJPEG

BLC/ HLC/ DWDR/ SSA

More than 50dB

Main Stream: 12M(1~20fps)/ 4K(1~25/30fps) , Sub Stream: D1 (1 ~ 25/30fps) , Third Stream: 1080P(1~25/30fps)

12M(4000x3000)/ 4K(3840x2160)/ 6M(3072x2048)/ 5M(2560x1920)/ 3M(2048x1536)/ 3M(2304x1296)/ 1080P(1920x1080)/ 1.3M(1280x960)/ 720P(1280x720)/ D1(704x576/704x480) / VGA(640x480)/CIF(352x288/342x240)

Off / On (4 Zone, Rectangle)

Privacy Mask, Active Tampering Alarm

Auto (ICR)/Color/B/W

Off / On (4 Zone)

1 Channel

1 Channel

G.711a / G.711u/AAC

2 Channel In

1 Channel Out

Supports

Supports

HTTP/HTTPS; TCP;ARP;RTSP;RTP;UDP;SMTP;FTP; DHCP;DNS;DDNS;PPPOE;IPv4/v6;SSL, ICMP, QoS; UPnP; NTP; Bonjour;802.1x;Multicast;ICMP;IGMP;SNMP, ONVIF (Profile S), PSIA, CGI

Tripwire, Intrusion, Object Abandoned/Missing, Face Detection, People Counting, Heat Map

RJ-45 (10/100Base-T)



*Product casing and specifications are subject to change without prior notice

CP- UNC-TH4KZR5-VM

4K Network Array Bullet Camera - 50Mtr.



Feature

User Account
Smart Phone
IR
Micro SD
Operating Temperature
Power Source
Power Consumption
Weatherproof Standard
Casing
Dimension
Weight

Specification

20 Users
iPhone, iPad, Android Phone
Array Range of 50 Mtr.
Max 128GB
-40°C~+60°C , Less than 95%RH
DC12V, PoE+(802.3at)
<13W
IP67 & IK10
Aluminium Alloy
273.2mm×95.0mm×96.4mm (10.76"×3.74"×3.79")
1.12Kg