

CP- UNC-VD4K081L3-VM

4K Full HD IR Vandal Dome Camera - 30Mtr.



Main Features

- 1/2.5" 4K progressive scan CMOS
- 15fps@4K(3840×2160), 25/30fps@3M(2304×1296)
- H.265/ H.264 dual-stream encoding
- DWDR, Day/Night (ICR), 3DNR, AWB, AGC, BLC
- 4mm fixed lens
- IR Range of 30 Mtrs, IP67, IK10, PoE
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro, vOptimus Pro



*Product casing and specifications are subject to change without prior notice

CP- UNC-VD4K081L3-VM

4K Full HD IR Vandal Dome Camera - 30Mtr.



Feature

Image Sensor
Minimum Illumination
Effective Pixels
Shutter Speed
White Balance
Lens
Gain Control (AGC)
Back Light Compensation
Video Compression
S/N Ratio
Video Streaming
Resolution
Digital Zoom
Motion detection
Privacy Mask
ICR
ROI
Audio Input
Audio Output
Audio Compression
Alarm IN
Alarm Out
Bit Rate
Protocol
Smart Detection
Ethernet
User Account
Smart Phone

Specification

1/2.5" 8MP Progressive scan CMOS
0.05Lux/F1.6 (Color), 0Lux/F1.6(IR on)
3840(H)x2160(V)
Auto/Manual, 1/3(4)~1/100000s
Auto/Natural/Street Lamp/Outdoor/Manual
4mm
Auto/Manual
BLC / HLC / DWDR
H.265+/H.265/H.264+/H.264
More than 50dB
Main Stream: 4K(1~15fps)/ 3M(1~25/30fps) / Sub Stream: D1(1~25/30fps) / Third Stream: 720P(1~25/30fps)
4K(3840x2160)/6M(3072x2048)/5M(2560x1920)/ 3M(2048x1536)/ 3M(2304x1296)/ 1080P(1920x1080)/1.3M(1280x960)/ 720P(1280x720)/D1(704x576/704x480)
16x
Off / On (4 Zone, Rectangle)
Up to 4 areas
Auto (ICR)/Color/B/W
Off / On (4 Zone)
1 Channel
1 Channel
G.711a/ G.711Mu/ AAC/ G.726
1 Channel
1 Channel
CBR/VBR
IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP,RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF, PSIA, CGI
Tripwire, Intrusion, Object Abandoned/Missing, Face detect
RJ-45 (10/100Base-T)
10/ 20 Users
iPhone, iPad, Android Phone



*Product casing and specifications are subject to change without prior notice

CP- UNC-VD4K081L3-VM

4K Full HD IR Vandal Dome Camera - 30Mtr.



Feature

IR
No. of IR LEDs
Micro SD
Operating Temperature
Power Source
Power Consumption
Weatherproof Standard
Dimension
Weight

Specification

IR Range of 30 Mtr.
24 IR
Micro SD card 128GB
-30° C ~ +60° C, Less than 95% RH
DC12V, PoE (802.3af)
<5W
IP67 & IK10
Φ109.9mm×81mm
0.41kg (0.91lb)