

CP- UNR-4K6128R16-V2

128 Ch. H.265 4K Network Video Recorder



Main Features

- Up to 128 channel IP camera input
- Up to 12Mp resolution preview and playback
- Max 384Mbps incoming bandwidth
- Support 16 SATA III ports, up to 96TB, 4 USB(2 USB3.0), 1 eSATA port
- Support iSCSI and Mini SAS to expand storage space
- 2 HDMI / 1 VGA simultaneous video output
- Support Multi-brand network cameras
- Support RAID 0/1/5/6/10/50/60
- ONVIF Version 2.4 conformance
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS, KVMS Pro



CP- UNR-4K6128R16-V2

128 Ch. H.265 4K Network Video Recorder



Feature

Processor
IP Camera Input
Operating System
Two-way Talk
User Interface
Video Output
Compression
Video Resolution
Video Recording
Video Display Split
Motion Detection
Video Loss
Camera Blank
Alarm Input
Alarm Output
Hard Disk
Smart Phone
Trigger Events
HDD Management
Recording Mode
Search Mode
Playback
Backup Mode
Record Interval
Max User Account
Interface Ports
Ethernet
Protocols

Specification

Intel Quad-core Processor
128 channel
Embedded LINUX
1 channel Input, 1 channel Output, RCA
GUI
2 HDMI (up to 3840× 2160), 1 VGA, 4 HDMI (Optional)
H.265/H.264 / MJPEG
3840× 2160, 1920× 1080, 1280× 1024, 1280× 720, 1024× 768
384Mbps
The 1st screen: 1/4/8/9/16/25/36, The 2nd screen: 1/4/8/9/16
MD Zones: 396(22×18).
Supports
Supports
16ch, low level effective, green terminal interface
8 Channel, NO/NC Programmable, Green Terminal Interface
16 SATA III ports, up to 96TB, 1 eSATA
iPhone, iPad, Android
Recording, PTZ, Tour, Alarm Out, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tips
Single, Raid 0/1/5/6/10/50/60 (Support global HDD hot-spare)
Manual, Schedule (Regular, MD (Motion Detection), Alarm, IVS), Holiday, Stop
Time /Date, Alarm, MD and Exact Search (accurate to second)
128Mbps in Raid 5 mode, 64Mbps in single HDD mode
USB Device/Network/eSATA Device
1 ~ 120 min (default: 60 min), Pre-record: 1 ~ 30sec, Post-record: 10 ~ 300 sec
128 users
2 HDMI, 1 VGA, 4 USB ports(3 USB2.0, 1 USB3.0), 1 Mini SAS port, for storage expansion, 1 RS485, 1 RS232, 4 RJ45
4 RJ-45 ports (10/100/1000Mbps), 4 Ethernet Ports Joint Working or 4 Independent 1000Mbps Ethernet Ports
HTTP, HTTPs, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP,SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, IP Search , ONVIF 2.4, CGI Conformant





CP- UNR-4K6128R16-V2

128 Ch. H.265 4K Network Video Recorder



Feature

Power Supply
Power Consumption
Working Temp
Dimensions
Weight

Specification

AC100V~240V, 50~60Hz
<51W(without HDD)
-10°C ~ +55°C (+14°F ~ +131°F), 86 ~ 106kpa
485mm x 512.9mm x 133.2mm (19.1" x 20.2" x 5.2")
17.6kg (38.8 lb) (without HDD)

