

CP- UNR-204T2-V2

4 Ch. Network Video Recorder



Main Features

- Up to 4ch@1080P Real-time Live-view & Playback
- H.264Plus /H.264 dual codec decoding
- Up to 6Mp resolution preview & playback
- Max 80Mbps incoming bandwidth
- Support 2 SATA HDDs up to 12TB, 2 ports (1 RearUSB2.0, 1 FrontUSB2.0)
- HDMI / VGA simultaneous video output
- Support Multi-brand network cameras
- ONVIF Version 2.4 conformance
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS, KVMS Pro



**Product casing and specifications are subject to change without prior notice*

CP- UNR-204T2-V2

4 Ch. Network Video Recorder



Feature

Processor
IP Camera Input
Operating System
Two-way Talk
User Interface
Video Output
Compression
Video Resolution
Video Recording
Video Display Split
Motion Detection
Video Loss
Camera Blank
Smart Phone
Hard Disk
Trigger Events
Recording Mode
Search Mode
Playback
Backup Mode
Max User Account
Interface Ports
Record Interval
Ethernet
Protocols
Power Supply
Power Consumption
Working Temp
Dimensions
Weight

Specification

Dual-core embedded processor
4 channel
Embedded LINUX
1 channel Input, 1 channel Output, RCA
GUI
1 HDMI, 1 VGA
H.264+/H.264
1920×1080, 1280×1024, 1280×720, 1024×768
Max 80 Mbps, 6Mp, 5Mp, 4Mp, 3Mp, 1080P, 1.3Mp, 720P & etc.
1/4
MD Zones: 396(22×18).
Supports
Supports
iPhone, iPad, Android Phone
2 SATA III ports, up to 12TB
Recording, PTZ, Tour, Video Push, Snapshot, and Screen Tips
Manual, Schedule(Regular(Continuous), MD, Stop
Time /Date, MD and Exact Search (accurate to second)
Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection,Digital zoom
USB Device / Network
128 users
1 HDMI, 1 VGA, 2 ports (1 RearUSB2.0, 1 FrontUSB2.0), 1 RJ45
1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
1 RJ-45 port (10/100M) , 1 Independent 100Mbps Ethernet Port
HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter,PPPOE, DDNS, FTP, Alarm Server,ONVIF Version 2.4
DC12V/4A
<3W (without HDD)
-10 ~+55°C / 10~90%RH / 86~106kpa
375mm x 275mm x 53mm
1.5kg (without HDD)