

CP- UNR-7364R8**64 Ch. Network Video Recorder****Main Features**

- 64Ch. with 1080p Realtime Live View
- H.264/MJPEG dual codec decoding
- Max 256Mbps incoming bandwidth
- Support 8 SATA HDDs up to 32TB, 1 eSATA up to 16TB, 4 USB2.0
- HDMI / VGA simultaneous video output
- Support Multi-brand network cameras
- ONVIF Version 2.2 conformance
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS, KVMS Pro



**Product casing and specifications are subject to change without prior notice*

CP- UNR-7364R8

64 Ch. Network Video Recorder



Feature

Processor
IP Camera Input
Operating System
Two-way Talk
User Interface
Video Output
Compression
Video Resolution
Video Recording
Video Display Split
Motion Detection
Video Loss
Camera Blank
Alarm Input
Alarm Output

Hard Disk

Smart Phone
Trigger Events
Recording Mode
Search Mode

Playback

Backup Mode
Interface Ports
Max User Account
Record Interval
Ethernet
Protocols
Power Supply

Specification

Dual-core embedded processor
64 channel
Embedded LINUX
1 channel Input, 1 channel Output, RCA
GUI
1 HDMI, 1 VGA, 1TV
H.264 / MJPEG
1920 x 1080, 1280 x 1024, 1280 x 720, 1024 x 768 & etc.
Max 192 Mbps
1/4/8/9/16/25/36
MD Zones: 396(22x18).
Supports
Supports
16 channel
6 channel
8 SATA ports (8HDDs or 6HDDs+1CD/DVD-RW), up to 32TB, Raid (redundancy), 1 eSATA port (Max 4 SATA HDDs), up to 16TB
iPhone, iPad, Android, Windows Phone
Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Spot, Buzzer & Screen
Manual, Schedule(Regular(Continuous), MD, Alarm), Stop
Time/Date, Alarm, MD & Exact search (accurate to second), Smart search

Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom

USB Device / eSATA Device / Internal SATA burner/ Network
1 HDMI, 1 VGA, 1TV, 1 USB2.0, 1 RS485, 1 RS232, 1 RJ45
20 users
1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
2 RJ-45 port (10/100M/1000M)
HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, ONVIF Version 2.2
AC 100~240V, 50/60 Hz

CP- UNR-7364R8

64 Ch. Network Video Recorder



Feature

Power Consumption

Working Temp

Dimensions

Weight

Specification

75W(without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

440mm × 460mm × 89mm

6KG(without HDD)