

CP- UNR-7364R8-R

64 Ch. Network Video Recorder



Main Features

- Upto 64Ch.Camera Connection
- H.264/MJPEG dual codec decoding
- Max 256Mbps incoming bandwidth
- HDMI / VGA simultaneous video output
- Support 8 SATA HDDs up to 32TB, 1 eSATA up to 16TB, 4 USB2.0
- Support RAID 0, RAID 1, RAID 5, RAID 6, RAID 10
- Support Multi-brand network cameras
- ONVIF Version 2.2 conformance
- Mobile Software: CMOB
- CMS Software: KVMS

CP- UNR-7364R8-R

64 Ch. Network Video Recorder

Feature

Processor
Operating System
IP Camera Input
Two-way Talk
User Interface
Video Output
Compression
Video Resolution
Video Recording
Video Display Split
Motion Detection
Video Loss
Camera Blank
Alarm Input
Alarm Output
Smart Phone
Hard Disk
Trigger Events
Recording Mode
Search Mode

Playback

Backup Mode
Interface Ports
Record Interval
Max User Account
Ethernet
Protocols
Power Supply

Specification

Dual-core embedded processor
Embedded LINUX
64 channel
1 channel Input, 1 channel Output, RCA
GUI
2 HDMI, 1 VGA, 1TV
H.264 / MJPEG
1920 x 1080, 1280 x 1024, 1280 x 720, 1024 x 768
Max 192 Mbps
1/4/8/9/16/25/36
MD Zones: 396(22x18).
Supports
Supports
16 channel
6 channel
iPhone, iPad, Android, Windows Phone
8 SATA ports (8HDDs or 6HDDs+1CD/DVD-RW), up to 32TB, Raid (redundancy), 1 eSATA port (Max 4 SATA HDDs), up to 16TB
Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Spot, Buzzer & Screen
Manual, Schedule(Regular(Continuous), MD, Alarm), Stop
Time/Date, Alarm, MD & Exact search (accurate to second), Smart search
Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
USB Device / eSATA Device / Internal SATA burner/ Network
2 HDMI, 1 VGA, 1TV, 4 USB2.0, 1 RS485, 1 RS232, 1 RJ45
1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
128 users
2 RJ-45 port (10/100M/1000M)
HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, ONVIF Version 2.2
AC 100~240V, 50/60 Hz

CP- UNR-7364R8-R

64 Ch. Network Video Recorder

Feature

Power Consumption

Working Temp

Dimensions

Weight

Specification

75W(without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

440mm × 460mm × 89mm

6KG(without HDD)